

AROMAZYME™

Drain & Grease Trap Maintenance Odor Eliminator



ITEM# FGAZ

AROMAZYME™
Drain & Grease Trap Maintenance Odor Eliminator

WENCO® AROMAZYME™ is the next generation technology in microbial blends with superior degradation capability for multiple applications. Aromazyme exhibits a broad range of uses in the maintenance of drain lines and grease traps as well as improving septic and waste degradation with exceptional odor control using our famous signature scent!

Features:

- A stable consortium of safe Bacillus spores.
- A synergistic blend that works in concert to provide superior performance across multiple applications.
- Excretion of high levels of amylase, cellulase, lipase and protease enzymes.
- Ability to work under aerobic and anaerobic conditions.

Benefits:

- Drain lines and grease traps.
- Septic and waste treatment.
- Bathroom odor controller.

Recommended Application Feed Rates:

GREASE TRAPS

TRAP SIZE	DOSING*
200 gallon trap (27 ft ³ or 0.8m ³)	10 oz. (300ml) per day
500-1500 gallon trap (67-200 ft ³ or 1.9-5.7m ³)	18-20 oz. (530 – 590ml) per day
1,500 gallon trap or larger (<200 ft ³ or >5.7m ³)	32-40 oz. (950 – 1180 ml) per day

DRAIN LINES

RESIDENTIAL & HOTEL	FREQUENCY	NOTES	DOSING*
Slow running Drains	3-day start-up treatment	Run hot water for 30 seconds, dose product directly into drain. Dose when drain will not be used for several hours.	2-4 oz. per day (60-120 ml. per day)
Maintenance	Ongoing	Dose when drain will not be used for several hours.	2-4 oz. per day (60-120 ml. per day)
COMMERCIAL	FREQUENCY	NOTES	DOSING*
Slow running Drains	7-day start-up treatment	Dose at closing or during quiet hours	6-8 oz. per day (180 – 240 ml. / day)
Maintenance	Ongoing	Dose at closing or during quiet hours	4-8 oz. per week (120 – 240 ml. per day)
FLOOR DRAINS	FREQUENCY	NOTES	DOSING*
Start-up	Ongoing	Treat drains for 3-7 days to achieve better flow rates	Mix 32 oz. in 2 gal. of water (125 ml./L) to treat 6-8 drains
Maintenance	Ongoing	Dose weekly. Dose at closing or during quite hours.	Mix 32 oz. in 2 gal. of water (125 ml./L) to treat 6-8 drains

**Dosing guidelines are recommendations only. Higher dosing rates may be required based on the grease loading, types of food cooked and number of meals served.*

TECHNICAL PROPERTIES

Form.....Liquid
 Color.....White
 Fragrance.....Perfumed
 pH.....6.5 - 7.5
 Specific Gravity @ 75°F.....1.01
 Density @ 75°F.....8.45 lbs Per Gallon
 Viscosity @ 75°F.....Thin
 Effective pH Range.....5.0 - 8.0
 Stability.....1 Year Minimum

AVAILABLE SIZES

- ✓ **12x1 Quart Case**
100% Recyclable
- ✓ **4x1 Gallon Case**
Bottles Contain 25% PCR
Carton Contains 55% PCF
- ✓ **55 Gallon Drum**
Reconditioned, Reused

1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
B	PERSONAL PROTECTION

SDS Available 24 / 7 / 365
wencobrand.com



WENCO Brand
 CLEANING SYSTEMS



WALTER E. NELSON COMPANY
 (800) 929-2141 • www.walternelson.com

