

# NEW-TECH FLOOR SYSTEMS

# LIQUID SHIELD™

## Stain Resistant Floor Sealer

**WENCO® LIQUID SHIELD™** Floor Sealer & Finish, utilizes the latest formulation technology to provide stain protective properties in a combination seal and finish for all types of resilient tile. **LIQUID SHIELD™** provides superior durability and satin appearance with exceptional leveling properties ideally suited to be used as a finish. It's like having three products in one. A stain barrier seal that has the capability of resisting the passage of stain causing agents: coal tar, asphalt, anti-oxidants, urine, etc. which can damage the floor. A leveling sealer that provides a good base for multiple top coats of ultra high speed floor finish. And because of its superior durability and satin gloss, a top coat finish for money and labor saving economy.

### DIRECTIONS FOR USE

#### STAIN RESISTANT AGAINST

Asphalt/Coal Tar · Mustard · Ketchup Coffee · Tea · Lipstick · Rust · Urine · Shoe Polish · Neozone (Floor mat backing)

1. Thoroughly strip all old wax and seal from the floor using any **WENCO® BRAND** floor stripper according to the directions.
2. After stripping, rinse the floor thoroughly to insure a clean film free surface.
3. Apply **LIQUID SHIELD™** in a uniform, thin coat using a lamb's wool floor finish applicator or clean mop. If you are using a mop and a bucket, line the bucket with a new trash can liner to prevent contamination from bucket residue
4. Allow to dry for a 30 minutes. If the floor has an uneven appearance, apply a second coat. Allow to dry 30 minutes before applying any **WENCO® BRAND** Floor Finish.
5. Multiple coats of **LIQUID SHIELD™** can be applied for a "hard as nails" finish. Or the floor may be top coated with any **WENCO® BRAND** ultra high speed floor finishes for your UHS system.



ITEM# **FGLSH**



**LIQUID SHIELD™**  
Stain Resistant Floor Sealer

#### TECHNICAL PROPERTIES

Form.....Liquid  
 Color.....Milky White  
 pH.....8.5 - 9.0  
 Specific Gravity @75°F.....1.01  
 Density @ 75°F.....8.4 lbs Per Gallon  
 Nonvolatile Solids.....18% +/-0.3%  
 Total Solids.....28.7%  
 Zinc Content.....None  
 Stability.....1 Year Minimum  
 Slip Resistance.....Meets ASTM D 2047

#### AVAILABLE SIZES

- ✓ **4x1 Gallon Case**  
Bottles Contain 25% PCR  
Carton Contains 55% PCF
- ✓ **5 Gallon Pail**  
100% Recyclable
- ✓ **55 Gallon Drum**  
Reconditioned, Reused

<b>1</b>	<b>HEALTH</b>
<b>0</b>	<b>FLAMMABILITY</b>
<b>0</b>	<b>REACTIVITY</b>
<b>B</b>	<b>PERSONAL PROTECTION</b>

SDS Available 24 / 7 / 365  
[wenco.com](http://wenco.com)



**WENCO** Brand  
CLEANING SYSTEMS



**WALTER E. NELSON COMPANY**  
 (800) 929-2141 • [www.walternelson.com](http://www.walternelson.com)

