

NEW-TECH FLOOR SYSTEMS MASTERPIECE™

Thermacrylic Floor Finish

WENCO® MASTERPIECE™ floor finish is a high solids, 22% thermacrylic floor finish. It is a hard finish with very high gloss. It spray buffs beautifully. It is heat sensitive. With the heat furnished with high speed floor machine it softens and can be dry buffed to original gloss. It becomes hard after being buffed. **MASTERPIECE™** has long extended gloss life without buffing.



ITEM# **FCMASTER**

MASTERPIECE™
Thermacrylic Floor Finish

DIRECTIONS FOR USE

PREPARATION OF FLOOR

Thoroughly strip floor, using a good quality ammoniated stripper or a stripper designed for removing modern metal interlock finish. Rinse well. A neutralizing rinse followed by a clear water rinse is recommended for best results.

APPLICATION

Apply first coat. Allow to dry for 30-40 minutes. Apply second coat and let dry. Apply third coat if needed. As with all finishes best results are obtained by application to well sealed floor.

MAINTENANCE

Use standard daily maintenance procedures. Spray buffing, especially with a high speed machine, will greatly enhance beauty and wear of finish.

TECHNICAL PROPERTIES

Form.....Liquid
Color.....Milky White
pH.....8.0 - 8.5
Specific Gravity @75°F.....1.031
Density @ 75°F.....8.58 lbs Per Gallon
Nonvolatile Solids.....22% +/-0.3%
Stability.....1 Year Minimum
Slip Resistance.....Meets ASTM D 2047

AVAILABLE SIZES

- ✓ **4x1 Gallon Case**
Bottles Contain 25% PCR
Carton Contains 55% PCF
- ✓ **5 Gallon Pail**
100% Recyclable
- ✓ **55 Gallon Drum**
Reconditioned, Reused

1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
B	PERSONAL PROTECTION

SDS Available 24 / 7 / 365
wenco.com



WENCO Brand
CLEANING SYSTEMS



WALTER E. NELSON COMPANY
(800) 929-2141 • www.walternelson.com

