

NEW-TECH FLOOR SYSTEMS

SOLID ICE™

Premium 25% Floor Finish



ITEM# **FCSICE**

SOLID ICE™
 Premium 25% Floor Finish

WENCO® SOLID ICE™ is the leading solution for proven performance and durability in floor finish. It is designed specifically to achieve outstanding performance when used in a high speed maintenance program. This formulation will help to reduce your labor costs by using fewer coats while increasing efficiency and optimizing your floor care program. Unlike many high solids finishes, **SOLID ICE™** goes down with ease; no drag or bubbling. Smooth leveling makes this finish stand out from the rest. It can be applied to almost all type of flooring; VCT tile, pure vinyl, linoleum etc. This finish is a self sealing finish*. It is extremely durable with superior shine that resists black heel marking. *For old, worn or badly damaged, using any **WENCO® Brand sealer** will enhance the gloss.

DIRECTIONS FOR USE

FLOOR PREPARATION

1. Thoroughly strip floor with **WENCO NEW-TECH IMPLOSION™** stripper according to directions.
2. After stripping, make sure floor is clean and residue free.

APPLICATION

1. Using a clean mop bucket lined with a trash can liner to prevent contamination, pour **SOLID ICE™** into the mop bucket.
2. Using a clean finish mop, saturate with finish. Place the mop in the wringer and tamp down to remove excess finish. Do not wring out.
3. Apply finish to the floor in thin to medium coats.
4. Allow each coat to dry a minimum of 20 – 30 minutes.
5. Apply multiple coats until desired gloss is achieved.

MAINTENANCE

1. Dust mop entire floor surface.
2. Using a clean mop & bucket, mix **WENCO AROMA CLEAN™** neutral pH cleaner and/or **WENCO NUTRA QUAT 64™** according to directions.
3. Damp mop floor as needed. No rinsing required.

TECHNICAL PROPERTIES

Form.....Liquid
 Color.....Milky White
 Fragrance.....None
 pH.....8.0 - 8.5
 Specific Gravity @75°F.....1.03
 Density @ 75°F.....8.6 lbs Per Gallon
 Nonvolatile Solids.....25% +/-0.3%
 Stability.....1 Year Minimum
 Slip Resistance.....Meets ASTM D 2047

AVAILABLE SIZES

- ✓ **4x1 Gallon Case**
Bottles Contain 25% PCR
Carton Contains 55% PCF
- ✓ **5 Gallon Pail**
100% Recyclable
- ✓ **55 Gallon Drum**
Reconditioned, Reused

1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
B	PERSONAL PROTECTION

SDS Available 24 / 7 / 365
wencobrand.com



WENCO Brand
 CLEANING SYSTEMS



WALTER E. NELSON COMPANY
 (800) 929-2141 • www.walternelson.com

